

## **Ocloc New Zealand** Manufactured in Australia / Distributed by Eckford Engineering NZ

Material: G450 high tensile steel for strength

**Coating:** GALFAN Coating 5% Aluminium, Rare Metals, 95% Zinc, the ultimate in corrosive resistant coating for durability

Thickness: CV 1.6mm thick Galfan

BV 1.8mm thick Galfan

#### Length: 1.05m

- Ocloc V fits onto the round or flat , on a half round post
- No sharp edges, ideal for under vine management
- No need for new toxic replacement posts
- No new wooden posts, reduces your vineyards carbon footprint
- All Ocloc products are carbon offset
- Maintain your organic status
- You will not have to cut staples or remove plastic clips
- No more posts to the broken post graveyard
- **Ocloc V** application requires a side by side, 4-wheeler or equivalent, petrol rammer, impact driver or drill
- Find broken post repair with Ocloc V with one pass
- 4 x 75mm shark tooth screws supplied
- **Ocloc V** is an inexpensive install that alleviates the expense of tedious traditional treated wooden post replacement and the ecological footprint legacy they create



### Ocloc products are carbon neutral — 100% carbon offset –



For further details please contact


Eckford Engineering Phillip Gleeson: 027 275 9057 Sam McConway: 027 422 4738

oclocnz@eckford.co.nz www.ocloc.com.au



# **Ocloc New Zealand**

### Manufactured in Australia / Distributed by Eckford Engineering NZ




Ocloc V-NZ profile



Ocloc half post repaired with Ocloc~V



Ocloc V-NZ - repaired post Marlborough



Half round post




Ocloc V-NZ - ramming



Shark Tooth Bugle Batten Screw, 75mm come in boxes of 500.





Half round post



Ocloc V-NZ - screwing



Watch video

### Ocloc products are carbon neutral — 100% carbon offset —



For further details please contact

Eckford Engineering Phillip Gleeson: 027 275 9057 Sam McConway: 027 422 4738

oclocnz@eckford.co.nz www.ocloc.com.au